



4 in. Square Box, Welded, 2-1/8 in. Deep with AC/MC/Flex Clamps, Four Knockouts, BOX-LOC® Series, MS Bracket, Flush

By RACO
Catalog # 243



4 in. Square Box, Welded, 2-1/8 in. Deep with AC/MC/Flex Clamps, Three 1/2 in. KO's and One TKO, BOX-LOC®, MS Bracket, Flush

Features

- Welded steel construction with "MS" BOX-LOC® bracket which allows for positioning on either side of stud
- 4 in. square x 2-1/8 in. deep
- BOX-LOC® Bracket is a snap to install. Place the bracket on the open side of the stud first. Slots in the bracket engage the lip of the stud
- BX clamps provided for steel and alum armored cable, MCI cable, MCI-A cable, and flexible conduit
- TKO® Knockouts allow for design and installation flexibility
- Supplied with three 1/2 in. and one 1/2-3/4 in. TKO® knockouts
- Combination Phillips/slotted screw heads
- 29.5 cu. in. capacity
- Acceptable for use in 2-hour fire rated walls

Specifications

Certified Listed	UL Listed
Buy American Compliant	Contact Manufacturer
EU RoHS Indicator	Contact Manufacturer

Configuration

Knockouts	<ul style="list-style-type: none"> • 1/2 in • 1/2 - 3/4 in Combination (TKO)
Bracket Type	MS, for Metal Studs
Number of Gang(s)	2-Gang

Current

Power Distribution Features	Fire Rated
-----------------------------	------------

Dimensions

Cubic Capacity	30.3 cu.in
Depth	2.125 in
Size	4 in
Actual Depth	2.188 in
Raised Ground	No
Width	5.5 in
Weight	1.068 lb.
Height	4.625 in

General

Wiring System	Armored Cable/Metal Clad/MCI-A/Flex
Series	BOX-LOC® Series
Color	Gray
Type	Box
Fire Resistance	Yes
Material	Steel
Drawn or Welded	Welded
UPC	050169002438

Logistics

Packaging Type	No Packaging
Carton Quantity	25
Pallet Quantity	1250

Product Assets

- [Catalog \[English\]](#)
- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)