

H361AWA

Safety switch, heavy duty, fusible, 30A,
600 VAC/VDC, 3 poles, 20 hp, NEMA 12K,
appleton powertite receptacle



Main

Product	Receptacle Switch
For Use With	Plug ACP3034BC Appleton Powertite
Current Rating	30 A
Enclosure Rating	NEMA 3R/12 galvanized steel
Horsepower Rating	5 Hp 480 V AC 50...60 Hz 3 phase NEC 240.6 15 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 7.5 Hp 600 V AC 50...60 Hz 3 phase NEC 240.6 20 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 5 hp 250 V DC NEC 240.6
Disconnect Type	Fusible disconnect switch
Short Circuit Current Rating	10 KA 200 kA
Mounting Type	Surface
Number of Poles	3
Phase	3 phase
Electrical Connection	Receptacle
Certifications	UL Listed
Voltage Rating	600 V AC 250 V DC
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Wire Configuration	4-wire

Complementary

Width	10.5 in (266.70 mm)
Height	16.5 in (419.10 mm)
Maximum Depth	7 in (177.80 mm)
Tightening torque	45 Lbf.in (5.08 N.m) AWG 6) 40 Lbf.in (4.52 N.m) AWG 8) 35 lbf.in (3.95 N.m) AWG 14...AWG 10)

Ordering and shipping details

Category	00124 - H&HU SW,W/APPLETON RECPT - WA
Discount Schedule	DE1
GTIN	00785901777359
Nbr. of units in pkg.	1
Package weight(Lbs)	13 lb(US) (5.90 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------