



**HSB34H6PF10, Heat Shrink Tubing,
0.75" ID Min.(Exp.), 0.22" ID Max.
(Rec.), #6 - 2, Polyolefin, Thick
Wall, Black, Shrink ratio-3:1, 600V.**



By Burndy
Catalog # [HSB34H6PF10](#)

Heat Shrink Tubing, 0.75" ID Min.(Exp.), 0.22" ID Max.(Rec.), #6 - 2, Polyolefin, Thick Wall, Black, Shrink ratio-3:1, 600V.

General

Catalog Number	HSB34H6PF10
Connector Type	HEAVY WALL TUBES
Material	Cross-linked Polyolefin
UPC	781810214800

Conductor Related

Conductor Range	#6 AWG to #2 AWG
Conductor Size	6AWG - 2AWG

Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM

UL Listed	Yes
-----------	-----

Logistics

Carton Quantity	250
-----------------	-----

Product Assets

- [Catalogs - BURNDY Master Catalog - Section D - Shrink Tubing](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide](#)
- [Product Cross Section Image\(s\) - BUR_HSB35H6PF25_LineArt](#)
- [Sales Drawings - SD211942-01](#)
- [Specifications - HSB34H6PF10 Specification Sheet French](#)
- [Specifications - HSB34H6PF10 Specification Sheet](#)
- [Video - Heat Shrink Product Overview & Installation](#)