

# Lay-In Lugs

## Dual Rated - Aluminum

### Features


- 90° C temperature rating
- Single hole assembly
- Provides positive grounding points in load centers or other enclosures

### Applications

- For use with copper or aluminum conductor
- Terminates an electrical conductor to facilitate mechanical connection

### Standard Material

- Aluminum
- Steel screw



| Catalog Number | UPC   | Recommended Torque in Lbs. | Bolt Size    | Unit Carton | Ship Case | Weight/Case | Wire Range Min. - Max. | Inches |        |        |       |
|----------------|-------|----------------------------|--------------|-------------|-----------|-------------|------------------------|--------|--------|--------|-------|
|                |       |                            |              |             |           |             |                        | A      | B      | C      | D     |
| <b>810</b>     | 18210 | 35                         | <b>1/4"</b>  | 25          | 250       | 6           | #14 - #4               | 1.0981 | .3906  | .75    | .193  |
| <b>811</b>     | 18220 | 50                         | <b>1/4"</b>  | ---         | 100       | 7           | #14 - 1/0              | 1.50   | 1.6099 | 1.4375 | .25   |
| <b>812</b>     | 18230 | 275                        | <b>5/16"</b> | ---         | 50        | 10          | 6 - 250 MCM            | 2.2031 | 2.2031 | 1.7031 | .3125 |