

Product data sheet

Specifications



Overload Relay, Motor Logic, solid state overload relay, NEMA Size 2, 3 pole, 15A to 45A, 600VAC, separate mount

9065SF220

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Motor Logic
Thermal overload type	Solid state

Complementary

NEMA size	2
Phase	3 phase
Mounting Support	Panel
[Ue] rated operational voltage	600 V AC
Height	3.5 in (89.2 mm)
Width	4.3 in (108.7 mm)
Depth	3.5 in (89.2 mm)

Ordering and shipping details

Category	US10CP121662
Discount Schedule	0CP1
GTIN	785901750000
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.10 in (12.954 cm)
Package 1 Width	5.30 in (13.462 cm)
Package 1 Length	6.20 in (15.748 cm)
Package weight(Lbs)	21.440 oz (607.813 g)

Contractual warranty

Warranty	18 months
----------	-----------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No