

Reducing Bushings and Couplings

2 TO 1/2 INCH REDUCING BUSHING



Catalog NumberPRRE61

UPC784011209286

Description

RE style reducers reduce conduit hubs to a smaller size. They are provided with an integral bushing to prevent conductor damage and full, clean cut threads for ease of assembly.

Application

- Reduce conduit hubs to a smaller size

Features

- RE style reducers reduce conduit hubs to a smaller size
- Provided with an integral bushing to prevent conductor damage
- Full, clean cut threads for ease of assembly

General Information

|                 |                                          |
|-----------------|------------------------------------------|
| Trade Size      | 2                                        |
| Material        | FERROUS METAL                            |
| Material        | FERROUS METAL                            |
| Exterior Finish | A nominal .002 inch (2 mil) red urethane |
| Interior Finish | A nominal .002 inch (2 mil) red urethane |

Dimensions

|                         |          |
|-------------------------|----------|
| Nominal Weight (Pounds) | 1.1      |
| Pipe Size (Inches)      | 2 to 1/2 |

Standards

|         |                                      |
|---------|--------------------------------------|
| NEC/CEC | Class III                            |
| NEC/CEC | Class II, Division 1, Groups E, F, G |



|         |                                   |
|---------|-----------------------------------|
| NEC/CEC | Class II, Division 2, Groups F, G |
|---------|-----------------------------------|

|         |                                            |
|---------|--------------------------------------------|
| NEC/CEC | Class I, Division 1 & 2, Groups A, B, C, D |
|---------|--------------------------------------------|

## Technical Specification Documents

---

|                                   |                      |
|-----------------------------------|----------------------|
| Specification Guide (1995 Master) | AVAILABLE ON WEBSITE |
|-----------------------------------|----------------------|

|                                   |                      |
|-----------------------------------|----------------------|
| Specification Guide (2004 Master) | AVAILABLE ON WEBSITE |
|-----------------------------------|----------------------|

|                                   |                      |
|-----------------------------------|----------------------|
| Installer Certification and Tools | AVAILABLE ON WEBSITE |
|-----------------------------------|----------------------|

|                            |                      |
|----------------------------|----------------------|
| Chemical Resistance Charts | AVAILABLE ON WEBSITE |
|----------------------------|----------------------|

|                            |                      |
|----------------------------|----------------------|
| Performance Specifications | AVAILABLE ON WEBSITE |
|----------------------------|----------------------|

## Technical Information

---

|                       |          |
|-----------------------|----------|
| Fitting Configuration | REDUCING |
|-----------------------|----------|

|              |         |
|--------------|---------|
| Fitting Type | BUSHING |
|--------------|---------|

|                  |         |
|------------------|---------|
| Product Category | FITTING |
|------------------|---------|

|                |                                 |
|----------------|---------------------------------|
| Product Family | Reducing Bushings and Couplings |
|----------------|---------------------------------|

|                  |          |
|------------------|----------|
| Trade Size Range | 2 to 1/2 |
|------------------|----------|

## Notes

---

- All REC, RE, and PLGs meet Class I, Division 1 & 2, Groups C, D. REs & PLGs meet the above standards only when used in conjunction with hazardous location fittings.
- Suitable for Groups A & B.