

Fuse terminal Screw terminal for inch fuse link 1/4'X1' and 1/4'X1 1/4'



Figure similar

Model	
Product brand name	ALPHA
Type of light source / as fault indicator	without
Design of the fuse link	others
Design of fuse holder	without
General technical data	
Insulation material	thermoplastic
Terminal contact spacing	10 mm
Supply voltage	
Type of voltage / for supply of the fault indicator	others
Protection class	
Combustibility class acc. to UL 94	Other
Main circuit	
Operating voltage / rated value	250 V
Operating current / rated value	6.3 A

Appearance			
Color	miscellaneous		
Product details			
Product component / required / connection plate	No		
Number			
Number of terminal levels	1		
Connections			
Connectable conductor cross-section / stranded	1.5 mm²		
• maximum			
Connectable conductor cross-section			
• solid			
— minimum			1 mm²
— maximum			1 mm²
• finely stranded			
— with core end processing / minimum			0.75 mm²
— with core end processing / maximum	1.5 mm²		
Type of electrical connection			
• 1	screw-type terminal		
• 2	screw-type terminal		
Position / of the terminal	lateral		
Mechanical Design			
Height / with lowest-profile installation	42 mm		
Length	57 mm		
Mounting type	DIN rail 35 mm		
Material / of the insulating body	Thermoplast		
General Product Approval		Declaration of Conformity	
		other	



CSA



UR



EG-Konf.

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1011-1SF30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WA1011-1SF30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1SF30

CAX-Online-Generator

<http://www.siemens.com/cax>

