

Product data sheet

Characteristics

8910DPA53V02DFJ2

Contactor, Definite Purpose, 50A, 3 pole, 30HP at 575VAC, 3 phase, 110/120VAC 50/60Hz coil, with 60A Class J fuses



Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	50 A
Number of Poles	3P
Pole contact composition	3 NO
Range of Product	DPA

Complementary

Maximum Horse Power Rating	3 Hp 115 V AC, 1 phase 10 Hp 230 V AC, 1 phase 15 Hp 230 V AC, 3 phase 30 Hp 460 V AC, 3 phase 30 hp 575 V AC, 3 phase
Locked rotor rated current	300 A 277 V AC 250 A 460 V AC 200 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	3 phase
Electrical Connection	Quick connect terminals Box lugs
Device Composition	Fuse holder

Environment

Product Certifications	UL Recognized[RETURN]CSA
------------------------	--------------------------




Ordering and shipping details

Category	US1CP1B21345
Discount Schedule	CP1B
GTIN	785901185161
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.0000000000 in (15.24 cm)
Package 1 Width	7.300 in (18.542 cm)
Package 1 Length	7.50 in (19.05 cm)
Package 1 Weight	3.0005 lb(US) (1.361 kg)

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 months
----------	-----------