

Conduit Unions UNF & UNY Unions

1-1/2 INCH FEMALE-TO-MALE (F/M) ALUMINUM UNY UNION



Catalog Number PRUNY505SA
UPC 784011219407

Description

PVC coated UNY unions are used to connect conduit to a conduit fitting, junction box, or device enclosure. One end is a male thread and the other is female.

Application

- Applicable for Hazardous Locations

Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 13 trade sizes from 1/2" through 6"
- Sealing sleeves on all conduit openings
- Molded PVC gasket seals fitting

General Information


Trade Size	1-1/2
Material	ALUMINUM
Material	ALUMINUM
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane

Dimensions

Length (Inches)	3.56
Max Diameter (Inches)	3.5

Standards

CSA	C22.2 No. 30
NEC/CEC	Class II, Division 1, Groups E, F, G
NEC/CEC	Class I, Division 1 & 2, Groups C, D
NEC/CEC	Class III
NEC/CEC	Class II, Division 2, Groups F, G
UL 1203	E476062



SAFETY US
E476062



Technical Specification Documents

Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Installer Certification and Tools	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Chemical Resistance Charts	AVAILABLE ON WEBSITE
----------------------------	----------------------

Performance Specifications	AVAILABLE ON WEBSITE
----------------------------	----------------------

Technical Information

Fitting Configuration	F/M
-----------------------	-----

Fitting Type	UNION
--------------	-------

Product Category	HAZARDOUS LOCATION FITTING
------------------	----------------------------

Product Family	Conduit Unions UNF & UNY Unions
----------------	---------------------------------

Rating	Hazardous Location
--------	--------------------