

YC4C8, Copper C-Shape Connector

By Burndy
Catalog # YC4C8



CU Compression C Shape Compression Connector, 600 Volts to 35 kV, Run: 6 Sol. - 4 Str., Tap: 8 Sol. - 8 Str.

Features

- Range-taking connector lowering inventory requirements
- Compact size, easy to tape and insulate connection
- High conductivity wrought copper provides low resistance and excellent electrical conductivity

Application

For Making Tap Or Parallel Copper Connections

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	No
Certification - UL Recognized	Yes
Industry Standard(s)	No
Buy America(n) Qualified	UL 486A;UL486B
Certification - ETL	Contact Manufacturer
Standards - Industry Standards Met	No
Standards - RoHS Compliance Status	UL 486A;UL486B
Certification - CSA Approved	CM
UL Listed	No
	Yes

Conductor

Conductor - Copper Solid Run Range	6 Sol. - 4 Str.
Conductor - Copper Solid Tap	8 AWG
Conductor - Copper Str Run Range	6 Sol. - 4 Str.

Conductor - Copper Str Tap	8 AWG
Conductor Type	Cu C Sol-Size

Dimensions

Dimension - L Length Overall mm	16 mm
Dimension - Height inch	0.73 in
Dimension - Height mm	0 mm
Dimension - Length Overall inch	0.62 in

General

Die Index	BG or 5/8
Trade Name	CRIMPIT™
Sub Brand	CRIMPIT
Plated	N
Type	YC-C Series
UPC 12 Digit	781810114254
UPC 14 Digit GTIN	00781810114254
Material	Copper
Plating Type	Unplated
UPC	781810114254

Logistics

Minimum Pack Quantity	1
Carton Quantity	100
Pallet Quantity	57600

Product Assets

[Catalog \[English\]](#)