

Selector switch, metal, NEMA 4X Spring return left & right Short lever, C Cam 1NO-1NC left, 1NO-1NC right 3 position Complete device white insert Non-illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)



Figure similar

Enclosure

Number of command points	1
--------------------------	---

Delivery state

• as a kit	No
------------	----

Actuator

Material of the actuating element	plastic
Number of contact modules	2
Type of unlocking device	without
Number of switching positions	3

Front ring

Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
Color of the front ring	black

General technical data

Product function	
------------------	--

• positive opening	Yes
Product component	
• Light source	No
Insulation voltage	
• rated value	600 V
Protection class IP	IP66
• of the terminal	IP20
Operating frequency maximum	600 1/h
Thermal current	10 A

Auxiliary circuit	
Number of NC contacts for auxiliary contacts	2
Number of NO contacts for auxiliary contacts	2
Operating current at AC-15	
• at 110 V rated value	60 A
• at 230 V rated value	30 A
• at 400 V rated value	15 A
• at 500 V rated value	12 A

Connections/Terminals	
Type of electrical connection	screw-type terminals
Tightening torque of the screws in the bracket	20 N·m
Tightening torque [lbf·in]	
• with screw-type terminals	8 lbf·in

Ambient conditions	
Ambient temperature	
• during operation	-35 ... +70 °C
• during storage	-40 ... +85 °C

Installation/ mounting/ dimensions	
Shape of the installation opening	round

Certificates/approvals	
-------------------------------	--

Further information	
Information- and Downloadcenter (Catalogs, Brochures,...)	http://www.siemens.com/industrial-controls/catalogs
Industry Mall (Online ordering system)	https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SX2CDBA2
Cax online generator	http://support.automation.siemens.com/WW/CAxOrder/default.aspx?lang=en&mlfb=US2:52SX2CDBA2
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)	https://support.industry.siemens.com/cs/ww/en/ps/US2:52SX2CDBA2
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)	http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SX2CDBA2&lang=en

last modified: 05/08/2019