

Product data sheet

Characteristics

8536SHO2V02H30S

NEMA Motor Starter, Type S, nonreversing,
Size 6, 540A, 400 HP at 460 VAC, up to 100
kA SCCR, 3 phase, 3 pole, Motor Logic, 120
VAC coil, open



Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

NEMA Size	6
Rated Current	540 A
Number of Poles	3P
Maximum Voltage Rating	600 V AC
Phase	3 phase
Type of Overload	Solid state Motor Logic class 10/20
Horsepower Rating	150 HP 200 V AC 200 HP 230 V AC 400 HP 460 V AC 400 HP 575 V AC
SCCR	Circuit-breaker 800 A maximum: 65 kA at 480 V AC Fuse J 600 A maximum: 100 kA at 600 V AC Fuse T 600 A maximum: 100 kA at 600 V AC Fuse RK1 600 A maximum: 100 kA at 600 V AC Fuse RK5 600 A maximum: 100 kA at 600 V AC
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control Circuit Type	Control circuit transformer
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Equipment	2 fuses (primary), 2 fuses (secondary)
Terminal Type	Screw clamp terminals
Height	28.06 in (712.72 mm)
Width	12.34 in (313.44 mm)
Depth	9.00 in (228.60 mm)

Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21195-8502,36 SH,SJ(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901924609
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.50 in (34.29 cm)
Package 1 Width	12.00 in (30.48 cm)
Package 1 Length	30.50 in (77.47 cm)
Package 1 Weight	78.98 lb(US) (35.825 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------