

Specifications



Photo is representative

Eaton WSR33542

Eaton Crouse-Hinds series Arktite WSR interlocked receptacle with enclosed disconnect switch, 30A, Three-wire, four-pole, Brass contacts, Solid door, Non-fused, Style 2, 7.5 HP/15 HP/20 HP, Copper-free alum, Spring door, 1", 240-600 Vac

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series Arktite WSR interlocked receptacle with enclosed disconnect switch
CATALOG NUMBER	WSR33542
UPC	782274019499
PRODUCT LENGTH/DEPTH	11.75 in
PRODUCT HEIGHT	27.69 in
PRODUCT WIDTH	7.25 in
PRODUCT WEIGHT	33 lb

Certifications and compliances

AREA CLASSIFICATION	Ordinary/Non-Hazardous Locations
STANDARDS TYPE	NEC/CEC
NEMA RATING	3R 4 12

Product specifications

DOOR STYLE	Solid
AMPERAGE RATING	30A
FUSING	Non-fused
GROUNDING STYLE	Style 2
CONFIGURATION	Three-wire, four-pole
MATERIAL	Copper-free aluminum
CONTACT MATERIAL	Brass
VOLTAGE RATING	240-600 Vac
HORSEPOWER	7.5 hp/15 hp/20 hp
RECEPTACLE STYLE	Spring door
TRADE SIZE	1"

Resources

CATALOGS	Arktite WSR/WSRD Interlock Receptacles catalog page
CERTIFICATION REPORTS	Arktite WSR/WSRD Interlock Receptacles with Enclosed Disconnect Switches Canadian certification Arktite WSR/WSRD Interlock Receptacles with Enclosed Disconnect Switches UL certification
INSTALLATION INSTRUCTIONS	IF 1315 - WSR Series Model 94 Interlock Receptacle IF 943 - WSR Series Model 82 Interlock Receptacle
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - WSR33542

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

