

K11A30U, Two Conductor Stacked Aluminum Panel Board Set Screw Connector

By Burndy
Catalog # [K11A30U](#)



Aluminum Universal Terminal, 1 Hole, 6 Str.- 300 Kcmil

Features

- Dual rated panelboard lugs
- Constructed from high strength, extruded aluminum alloy
- Electro tin-plated to provide low contact resistance

Application

For Aluminum And Copper Conductors

Specifications

Buy American Compliant	Contact Manufacturer
EU RoHS Indicator	Yes
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 300 kcmil
Conductor - AL Str Size	<ul style="list-style-type: none"> • 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil

Conductor - AL Str Size Range	6 Str.- 300 Kcmil
Conductor - Copper Solid Size	<ul style="list-style-type: none"> • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG
Conductor - Copper Solid Size Range	4 AWG-4/0 AWG
Number Of Conductors	2
Conductor Size	6 AWG-300 KCMIL
Conductor - Copper Str Size Range	6 Str.- 300 Kcmil
Conductor Type	<ul style="list-style-type: none"> • AL C Str-Size • CU C Str-Size • CU C Solid-Size

Configuration

Physical Attribute - Number of Holes	1
Connector Type	Stacked

Dimensions

Package Length	4.300 in
Package Width	3.750 in
Package Weight	0.910 lb.
Dimension - L Length Overall mm	76 mm
Dimension - Pad Width inch	1.02 in
Dimension - Height fraction	2 in
Dimension - Height inch	2.03 in
Package Height	3.400 in
Dimension - Height mm	51.6 mm
Dimension - Hole Size inch	0.33 in
Dimension - Hole Size mm	8 mm
Dimension - Screw Size inch	11/16
Dimension - Stud Size fraction	5/16
Dimension - Stud Size inch	5/16 in
Dimension - Thread Size	5/16 in
Dimension - Width inch	1.02 in
Dimension - Width mm	25 mm
Dimension - Bolt Hole Size inch	0.31 in
Dimension - Bolt Size fraction	5/16

Dimension - Length Overall 3.00 in
inch
Dimension - D inch 0.94 in
Dimension - N inch 0.47 in

Force Related

Installation Torque 275 LBS/in
Recommended in-lb

General

Material - Hardware Aluminum
Sub Brand UNIVERSAL TERM
Physical Attribute - Screw Type Allen
Plated Y
Type Bolted Lugs & Terminals
UPC 12 Digit 781810370261

UPC 14 Digit GTIN 00781810370261
Material Aluminum
Hex Key 3/4
Plating Type Tin plated
UPC 781810370261

Logistics

Minimum Pack Quantity 1
Carton Quantity 72
Pallet Quantity 2304

Operational

Temperature Rating 194

Product Assets

[Catalog \[English\]](#)



A Hubbell brand