



radiant Collection
radiant® Two Single-Pole Switches and Single Pole/3-Way Switch, Gray
Part No. RCD113GRY



More control, less space. This combination switch provides control of multiple lights or devices from a single location, while featuring an oversized primary switch for easy use. Designed to emulate the sleek lines of the collection's paddle switches, it delivers flexible, space-saving control with the sophisticated look of radiant. Made exclusively for use with screwless Wall Plates from the radiant Registered Collection, sold separately.

Features & Benefits

Offers installation flexibility with space-saving style, as part of the extensive offering from the radiant® Collection. Features durable, high-impact resistant thermoplastic construction.

Designed to install easily with a narrower back body and captivated mounting screws. Patented Snap-In Light Module (sold separately) transforms a combination switch into an illuminated switch in seconds.

More color options available to fit any style, including finishes to match current hardware and lighting trends. Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from the radiant® Collection.

Specifications

General Info

| | | | |
|---------------------|---|--------------------|-------------------------|
| Product Line | Pass & Seymour | Color | Gray |
| Finish | Satin | UPC Number | 785007233544 |
| Country Of Origin | China | Material | Thermoplastic |
| Features | Combination, Decorator Style, Locator Light | Switch Type | Paddle |
| Number of Switches | 3 | Application Sector | Residential |
| Wall Plate Included | No | Warranty Type | 1-Year Limited Warranty |
| Type | Switch | | |

Dimensions

| | | | |
|------------------|---------|------------------|---------|
| Product Width US | 1.29 in | Product Depth US | 1.59 in |
|------------------|---------|------------------|---------|

| | |
|-------------------|---------|
| Product Height US | 3.81 in |
|-------------------|---------|

Technical Information

| | | | |
|-------------|--------------------|---------------------|---------------|
| Load Rating | 15 A @ 120/125 VAC | Connection Location | Back and Side |
|-------------|--------------------|---------------------|---------------|

| | | | |
|------------------------|-------------------|-----------------|---|
| Terminal Accommodation | #14 AWG - #12 AWG | Number of Gangs | 1 |
|------------------------|-------------------|-----------------|---|

| | | | |
|------------|--------------|----------|------|
| Throw Type | Single Throw | Amperage | 15 A |
|------------|--------------|----------|------|

| | | | |
|-----------------|--------------------|-----------------------|-----|
| Number of Poles | 3-Way, Single Pole | Requires Neutral Wire | Yes |
|-----------------|--------------------|-----------------------|-----|

| | | | |
|----------------|--------|---------------|----------|
| Indoor/Outdoor | Indoor | Mounting Type | Wall Box |
|----------------|--------|---------------|----------|

| | | | |
|-----------------|-----|----------------------|--------------------------|
| Location Rating | Dry | Wire Connection Type | Push Wire, Wire Terminal |
|-----------------|-----|----------------------|--------------------------|

| | | | |
|---------|------------------|-----------|--|
| Voltage | 120 VAC, 125 VAC | Load Type | CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon |
|---------|------------------|-----------|--|
