



SKU: PTT-2R-250-Z

UPC: 0783669750102

Features & Benefits:

Description: Aluminum Pole Type Overhead Transformer Lug, Dual Rated, Conductor Range 250-10, 2 Ports, Right Handed

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	2
Number of Poles	1
Number of Ports / Wireways	2

Dimensions

Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	1.125
Height BX (IN)	2.25
Length (IN)	2.391
Length (mm)	60.7314
Mounting Bolt/Stud Length (mm)	101.6
Mounting Bolt/Stud Size (mm)	304.8
Weight (LB)	0.439
Weight BX (LB)	2.1232
Width (IN)	4
Width BX (IN)	5
Width (mm)	101.6

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----



Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	5/8

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 2
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366975010

Testing Standards

ANSI Specification	ANSI C119.6
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	NA
UL File Number	NA

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	250 kcmil - 10 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 10 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	10 Sol