



Industrial Spec Grade SingleTurnlok Registered 20A 480V Receptacle

## Features & Benefits

Compact, impact-resistant nylon face and body are ultrasonically welded together for unrivaled strength.

One piece, high-grade brass contacts offer excellent conductivity and heat-rise resistance.

Single-piece, solid brass mounting strap is free of easily loosened rivets found on other brands.

Accepts #14 - #10 AWG.

Face color coding by voltage facilitates locating and mating of proper devices.

Clearly marked NEMA configuration, rating, and third-party listing on each unit's face.

Side and external screw-pressure-plate back wire capability.

## Specifications

### General Info

Product Line	Pass & Seymour	Color	Black
UPC Number	785007282054	Country Of Origin	Mexico
Number of Receptacles	1	Features	Brass Mounting Strap
Outlet Type	Locking	Application Sector	Industrial
Wall Plate Included	No	Standard	UL498, CSA C22.2 No. 42
Warranty Type	1-Year Limited Warranty		

### Dimensions

---

Product Width US	1.61 in	Product Depth US	1.19 in
------------------	---------	------------------	---------

---

Product Height US	2.29 in
-------------------	---------

---

### Listing Agencies / 3rd Party Agencies

---

cULus ListingNumber	140596	cULus Listed	Yes
---------------------	--------	--------------	-----

---

### Additional Information

---

Product Environmental Profile	Yes
-------------------------------	-----

---

### Technical Information

---

Operating Temperature Min	-40 °C	Connection Location	Back and Side
---------------------------	--------	---------------------	---------------

---

Number of Wires	3	Operating Temperature Max	75 °C
-----------------	---	---------------------------	-------

---

Amperage	20 A	Number of Poles	Double Pole
----------	------	-----------------	-------------

---

Wire Size	14 - 10 AWG	Indoor/Outdoor	Indoor
-----------	-------------	----------------	--------

---

NEMA Configuration Code	L8-20R	Operating Temperature	-40°-75°C
-------------------------	--------	-----------------------	-----------

---

Wire Connection Type	Screw Terminals	Voltage	480.0 V
----------------------	-----------------	---------	---------

---

Environmental Conditions	Flammability: UL94 V2: Operating Temperature: Maximum continuous +75°C, minimum -40°C without impact
--------------------------	--

---