

Data sheet

US2:52SB2HAB

Design of the product		Selector switch, metal Maintained Long lever, H Cam 4 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)
Enclosure		Actuator round
Number of command points		1
Delivery state		
• as a kit		No
Actuator		
Design of the operating mechanism		selector switch
Material of the actuating element		plastic
Shape of the actuating element		Extended handle
Type of unlocking device		rotate-to-unlatch mechanism
Number of switching positions		4
Front ring		
Product component front ring		Yes
Design of the front ring		standard
Material of the front ring		metal
Color of the front ring		chrome
Holder		
Material of the holder		Metal
General technical data		
Product component		
• Light source		No
Degree of pollution		1
Protection class IP		IP66
Operating frequency maximum		600 1/h
Ambient conditions		
Ambient temperature		
• during operation		-35 ... +70 °C
• during storage		-40 ... +85 °C
Installation/ mounting/ dimensions		
Shape of the installation opening		round
Certificates/approvals		
Further information		

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SB2HAB>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SB2HAB>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SB2HAB>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SB2HAB&lang=en

last modified:

04/30/2019