


# Product data sheet

## Characteristics

# 9065SD05

Overload Relay, Type S, melting alloy,  
replacement overload, NEMA sizes 00, 0, 1, 3  
to 5 pole, 27A, 600VAC



### Main

Range of Product	Replacement Relay
Product destination	Starter
Thermal overload type	Melting alloy

### Complementary

NEMA size	0 00 1
Phase	3 phase
Number of thermal units required	3
Mounting Support	Mounting plate
[Ue] rated operational voltage	600 V AC
Height	4.00 in (101.6 mm)
Width	3.50 in (88.9 mm)
Depth	3.97 in (100.8 mm)

### Ordering and shipping details

Category	21661-9065 A,C,F,G,S(NOT SS)
Discount Schedule	CP1
GTIN	785901882312
Returnability	Yes
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.49 in (11.4 cm)
Package 1 Width	5.31 in (13.5 cm)
Package 1 Length	5.51 in (14.0 cm)
Package 1 Weight	15.20 oz (430.9 g)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

## Contractual warranty

---

Warranty	18 months
----------	-----------

---