

SNAPConnect® Heavy Duty  
Hospital Grade Tamper-  
Resistant/Weather Resistant  
AUTOGUARD® Self-Test GFCI  
Receptacle, 20A, Light Almond

By Hubbell Wiring Device-Kellems  
Catalog # [SNAPGFTW83LA](#)

Straight Blade SNAPConnect® Receptacle, GFCI, Tamper and  
Weather Resistant, Commercial Hospital Grade, Self-Test, 20A  
125V, 2-Pole 3-Wire Grounding, 5-20R.

Features

- Audible SNAP, indicates solid connection
- Patented shutter design for tamper-resistant protection
- Meets NEC requirements for TR (406.12) and WR (406.9), UV and corrosion resistance for harsh and damp applications
- Patented AUTOGUARD® Self-Test technology
- Protects against line and load reversal, no power to the face or downstream if device is miswired

Application

- Commercial Hospital Grade

General

|                          |                                                                                                                                                                                                                                |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Catalog Number           | SNAPGFTW83LA                                                                                                                                                                                                                   |
| Color                    | Light Almond                                                                                                                                                                                                                   |
| Environmental Conditions | Weather Resistant                                                                                                                                                                                                              |
| Item Type                | Self test GFCI receptacle                                                                                                                                                                                                      |
| Material                 | Nylon                                                                                                                                                                                                                          |
| Series                   | Hospital Grade                                                                                                                                                                                                                 |
| Size                     | 4.12 in x 1.75 in x 1.48 in                                                                                                                                                                                                    |
| Specifications           | <ul style="list-style-type: none"><li>• Base - Nylon</li><li>• Face - Nylon</li><li>• Contacts - Brass</li><li>• Mounting Screws - Stainless Steel</li><li>• Mounting Strap - Brass</li><li>• Power Contacts - Brass</li></ul> |
| Type                     | Tamper-Resistant, Weather Resistant                                                                                                                                                                                            |
| UPC                      | 783585746319                                                                                                                                                                                                                   |

Dimensions

|            |                             |
|------------|-----------------------------|
| Dimensions | 1.48 in x 1.75 in x 4.12 in |
|------------|-----------------------------|



|        |         |
|--------|---------|
| Height | 4.12 in |
| Length | 1.48 in |
| Width  | 1.75 in |

Electrical Ratings

|                           |              |
|---------------------------|--------------|
| Current / Amperage Rating | 20 A         |
| Phase                     | Single Phase |
| Voltage Rating            | 125 VAC      |
| Wattage                   | 2500 W       |

Conductor Related

|           |             |
|-----------|-------------|
| Wire Size | SNAPConnect |
|-----------|-------------|

Certifications And Compliance

|                      |                                        |
|----------------------|----------------------------------------|
| Industry Standard(s) | UL 943 and Meets All NEC® Requirements |
| Nema Rating          | 5-20R                                  |

Logistics

|                 |    |
|-----------------|----|
| Carton Quantity | 10 |
|-----------------|----|

Product Assets

- [Catalog Page - WDK A-17 Catalog Page](#)
- [Catalog Page - WDK K-7 Catalog Page](#)
- [Catalog Page - WDK L-5 Catalog Page](#)
- [Catalog Page - WDK L-14 Catalog Page](#)
- [Catalogs - WDK Catalog Full 2024](#)
- [Engineering Drawing - M14625\\_ACAD](#)
- [Installation Manuals - PD2986](#)
- [Sales Drawings - M14625](#)
- [Specifications - SNAPGFTW83LA](#)
- [Warranty - Industrial & Commercial Products](#)