



SKU: IK3-2

UPC: 0783669813609

Features & Benefits:

Description: Three Wire Copper Split Bolt, Conductor Range for Equal Main & Tap 2-6 Sol, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	3
Number of Poles	1

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	NA
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range for Equal Run & Tap Str	2 Str - 5 Str
Conductor Range for Equal Run & Tap Sol	3 Sol - 6 Sol
Conductor Range for Minimum Tap with Maximum Run	14 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Max Conductor Copperweld - Str	3 No. 7
Max Conductor Copperweld - Type A	3A

Dimensions

Drive Size Main	13/16
Drive Type Main	External Hex
Height (IN)	0
Height BX (IN)	2.25
Length (IN)	0
Weight (LB)	0.105
Weight BX (LB)	1.109
Width (IN)	0
Width BX (IN)	4.375
Wire Diameter Range Primary (IN)	0.162 - 0.258

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA

Material

Copper

Additional Technical Specifications
Conductor Type

Stranded

Bolt and Screw Sizes
Number of Wire Binding Screws per Port

1

Wire Binding Screw Size

NA

General
Bag Quantity

1

Carton Quantity Description

STD PACK QTY 10

Direct Burial

Yes

Dual Rated

No

NEMA Code

S-588-4

UPC Code

78366981360

Testing Standards
CSA File Number

LR-701570

CSA Standard

C22.2 No. 65

Prop65 Compliance

This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

UL Control Number

460C

UL / CULUS Specification

UL 467 Listed

UL File Number

E12822

Environment and Temperature
Temperature Rating

90°C

Color
Color

Copper

Voltage
Voltage Rating

35 kV