



SKU: ELT-7

UPC: 0783669257427

Features & Benefits:

Description:Permaground Copper Grounding E Crimp, Main Conductor Range 500-300, Main Rebar Size #5, Tap Range 3/0-6 Sol, Tap Rebar Size #3-#4, UL, CSA

Specs

Additional Class Attributes

Fixing Type	NA
ILSCOs Die Index Number	1011

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	2 Sol - 6 Sol
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 300 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	3/0 Str - 6 Str
Ground Rod Size	5/8
Rebar Size(s) Main	#5 (5/8)
Rebar Size(s) Secondary	#3 (3/8)

Dimensions

Height (IN)	2.672
Height BX (IN)	2
Height (mm)	67.8688
Length (IN)	1.325
Length (mm)	33.655
Weight (LB)	0.505
Weight BX (LB)	3.1
Width (IN)	0.875
Width BX (IN)	5
Width (mm)	22.225

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-3
UPC Code	78366925742

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL / CULUS Specification	UL 467 Listed

Environment and Temperature

Temperature Rating	NA
--------------------	----

Color

Color	Copper
-------	--------