

Specifications



Photo is representative

Eaton CES4233

Eaton Crouse-Hinds series Arktite CES receptacle, 30A/60A, Through feed, 2-wire, 3-pole, Brass or hard-drawn copper contacts, Style 2, 3 HP, Feraloy iron, Single-phase, Spring door, 1-1/4", Delayed action circuit breaking, 120-240/480 Vac

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series Arktite CES receptacle
CATALOG NUMBER	CES4233
UPC	782274127705
PRODUCT LENGTH/DEPTH	6.13 in
PRODUCT HEIGHT	12 in
PRODUCT WIDTH	7 in
PRODUCT WEIGHT	16.1 lb



Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class I, Division 2

Product specifications

TRADE SIZE	1-1/4"
GROUNDING STYLE	Style 2
CONFIGURATION	Two-wire, three-pole
PHASE	Single-phase
HORSEPOWER	3 hp
AMPERAGE RATING	30A/60A
VOLTAGE RATING	120-240 Vac/480 Vac
RECEPTACLE STYLE	Spring door
BACK BOX STYLE	Through feed
MATERIAL	Feraloy iron alloy
CONTACT MATERIAL	Brass Hand-drawn copper
TYPE	Delayed action circuit breaking

Resources

CATALOGS	Arktite CES and CPH Explosionproof Receptacles and Plugs catalog page
CERTIFICATION REPORTS	Arktite CES and CPH Explosionproof Receptacles and Plugs Canadian certification Arktite CES and CPH Explosionproof Receptacles and Plugs UL certification
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - CES4233

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

