



Material:

- The steel meets or exceeds the physical properties of ASTM A1011 GR 33, except with SS, ST & AL finishes.

Finishes:

- Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- Unistrut Defender (DF):** Conforms to ASTM A1059
- Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1 or SC3
- Everdur (E EG):** TBD
- Stainless Steel, Type 304 (SS):** ASTM A240, Type 304 *
- Stainless Steel, Type 316 (ST):** ASTM A240, Type 316 *
- Aluminum (AL):** TBD

* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Material & Finish Combinations:

Material / Finish	Part Number Suffix	Pipe Clamp Material / Finish	Fasteners (Screw & Nut) Material / Finish	Example
Electro-galvanized	EG	EG	EG	P1109EG
Hot-dipped galvanized	HG	HG	SS	P1109HG
Unistrut Defender	DF	DF	DF	P1109DF
Stainless Steel Type 304	SS	SS	SS	P1109SS
Stainless Steel Type 316	ST	ST	SS	P1109ST
Aluminum	AL	AL	AL	P1109AL
Copper Coated	CC	CC	CC	P1109CC
Everdur	EEG	EG	E	P1109EEG

Part No.	Nom. Pipe Size	A	B	C	Ga. (Thickness)	Finish	Product Weight / Piece (lbs)
P2558-05	1/2"	2-7/8"	9/32"	7/16"	1/8"	EG	0.23
P2558-05	1/2"	2-7/8"	9/32"	7/16"	1/8"	HG	0.243
P2558-05	1/2"	2-7/8"	9/32"	7/16"	1/8"	GR	0.23
P2558-05	1/2"	2-7/8"	9/32"	7/16"	1/8"	SS	0.23
P2558-05	1/2"	2-7/8"	9/32"	7/16"	1/8"	AL	0.03
P2558-07	3/4"	3-1/8"	9/32"	7/16"	1/8"	EG	0.26
P2558-07	3/4"	3-1/8"	9/32"	7/16"	1/8"	HG	0.275
P2558-07	3/4"	3-1/8"	9/32"	7/16"	1/8"	GR	0.26
P2558-07	3/4"	3-1/8"	9/32"	7/16"	1/8"	SS	0.26
P2558-07	3/4"	3-1/8"	9/32"	7/16"	1/8"	AL	0.09
P2558-10	1"	3-3/8"	9/32"	7/16"	1/8"	EG	0.31
P2558-10	1"	3-3/8"	9/32"	7/16"	1/8"	HG	0.328
P2558-10	1"	3-3/8"	9/32"	7/16"	1/8"	GR	0.31
P2558-10	1"	3-3/8"	9/32"	7/16"	1/8"	SS	0.31
P2558-10	1"	3-3/8"	9/32"	7/16"	1/8"	AL	0.1
P2558-12	1-1/4"	3-3/4"	9/32"	7/16"	1/8"	EG	0.35
P2558-12	1-1/4"	3-3/4"	9/32"	7/16"	1/8"	HG	0.371
P2558-12	1-1/4"	3-3/4"	9/32"	7/16"	1/8"	GR	0.35
P2558-12	1-1/4"	3-3/4"	9/32"	7/16"	1/8"	SS	0.35
P2558-15	1-1/2"	3-7/8"	9/32"	7/16"	1/8"	EG	0.39
P2558-15	1-1/2"	3-7/8"	9/32"	7/16"	1/8"	HG	0.413
P2558-15	1-1/2"	3-7/8"	9/32"	7/16"	1/8"	GR	0.39
P2558-15	1-1/2"	3-7/8"	9/32"	7/16"	1/8"	SS	0.39
P2558-15	1-1/2"	3-7/8"	9/32"	7/16"	1/8"	AL	0.13
P2558-20	2"	5-3/4"	7/16"	11/16"	1/4"	EG	0.94
P2558-20	2"	5-3/4"	7/16"	11/16"	1/4"	HG	0.996
P2558-20	2"	5-3/4"	7/16"	11/16"	1/4"	GR	0.94

P2558-20	2"	5-3/4"	7/16"	11/16"	1/4"	SS	0.94
P2558-20	2"	5-3/4"	7/16"	11/16"	1/4"	ST	0.94
P2558-20	2"	5-3/4"	7/16"	11/16"	1/4"	AL	0.35
P2558-25	2-1/2"	6-1/4"	7/16"	11/16"	1/4"	EG	1.14
P2558-25	2-1/2"	6-1/4"	7/16"	11/16"	1/4"	HG	1.208
P2558-25	2-1/2"	6-1/4"	7/16"	11/16"	1/4"	GR	1.14
P2558-25	2-1/2"	6-1/4"	7/16"	11/16"	1/4"	SS	1.14
P2558-25	2-1/2"	6-1/4"	7/16"	11/16"	1/4"	AL	0.41
P2558-30	3"	6-7/8"	7/16"	11/16"	1/4"	EG	1.33
P2558-30	3"	6-7/8"	7/16"	11/16"	1/4"	HG	1.409
P2558-30	3"	6-7/8"	7/16"	11/16"	1/4"	GR	1.33
P2558-30	3"	6-7/8"	7/16"	11/16"	1/4"	SS	1.33
P2558-30	3"	6-7/8"	7/16"	11/16"	1/4"	ST	1.33
P2558-35	3-1/2"	7-3/8"	7/16"	11/16"	1/4"	EG	1.52
P2558-35	3-1/2"	7-3/8"	7/16"	11/16"	1/4"	HG	1.611
P2558-35	3-1/2"	7-3/8"	7/16"	11/16"	1/4"	GR	1.52
P2558-35	3-1/2"	7-3/8"	7/16"	11/16"	1/4"	SS	1.52
P2558-35	3-1/2"	7-3/8"	7/16"	11/16"	1/4"	ST	1.52
P2558-40	4"	7-7/8"	7/16"	11/16"	1/4"	EG	1.76
P2558-40	4"	7-7/8"	7/16"	11/16"	1/4"	HG	1.865
P2558-40	4"	7-7/8"	7/16"	11/16"	1/4"	GR	1.76
P2558-40	4"	7-7/8"	7/16"	11/16"	1/4"	SS	1.64
P2558-40	4"	7-7/8"	7/16"	11/16"	1/4"	ST	1.64
P2558-50	5"	9"	7/16"	11/16"	1/4"	EG	1.98
P2558-50	5"	9"	7/16"	11/16"	1/4"	HG	2.098
P2558-50	5"	9"	7/16"	11/16"	1/4"	GR	1.98
P2558-50	5"	9"	7/16"	11/16"	1/4"	SS	1.98
P2558-50	5"	9"	7/16"	11/16"	1/4"	ST	1.98
P2558-60	6"	10"	7/16"	11/16"	1/4"	EG	2.25
P2558-60	6"	10"	7/16"	11/16"	1/4"	HG	2.385
P2558-60	6"	10"	7/16"	11/16"	1/4"	GR	2.25
P2558-60	6"	10"	7/16"	11/16"	1/4"	SS	2.28
P2558-60	6"	10"	7/16"	11/16"	1/4"	ST	2.28
P2558-80	8"	12"	9/16"	9/16"	1/4"	GA	2.385
P2558-100	10"	14"	9/16"	11/16"	1/4"	GA	2.25

Project:

Architect / Engineer:

Date:

Phone:

Contractor:

Address:

Notes:

Approval Stamp: