BURNDY®

YGA262N Compression Grounding Lug, 2/0 AWG Cu, 2-Hole, 1/2" Stud, 1-3/4" Spacing

By Burndy
Catalog # YGA262N

HYGROUND® Grounding Irreversible Compression Terminals

Features

- Irreversible Compression Grounding Lug
- Inspection port to ensure proper cable insertion
- UL 467 Listed, acceptable for direct burial in earth or concrete
- Prefilled with PENETROX Oxide Inhibiting Compound and strip sealed
- 2 Stud Holes, 1/2" with 1-3/4" Spacing
- Die Index: 13

Application

For Grounding Applications And Direct Burial In Earth Or Concrete

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Size	2/0 Str.
Conductor - Copper Str Size Range	2/0 AWG
Conductor Type	• CU C Solid-Size
	• CU C Str-Size

Configuration

Physical Attribute - Number of Crimps Required	2
Connector Type	Terminal

Dimensions

Dimension - Outside Diameter inch	0.56 in
Dimension - L Length Overall mm	126 mm
Dimension - Pad Width inch	0.81 in
Dimension - Hole Size inch	0.56 in
Dimension - Hole Size mm	14 mm
Dimension - Strip Length inch	1-9/16
Dimension - Stud Size fraction	1/2
Dimension - Stud Size inch	1/2
Dimension - Width fraction	1/2 in
Dimension - Width inch	0.53 in
Dimension - B Length fraction	1-4/9 in
Dimension - B Length inch	1.45 in
Dimension - Bolt Hole Size inch	0.52 in
Dimension - Bolt Size inch	0.50 in
Dimension - Length Overall inch	4.97 in
Dimension - N inch	0.62 in

General

Die Index	13
Trade Name	HYLUG™
Sub Brand	HYLUG
Color Code	Black
Plated	N
Type	Terminals
UPC 12 Digit	781810220313
UPC 14 Digit GTIN	00781810220313
Material	Copper
Plating Type	Unplated
UPC	781810220313

Logistics

Minimum Pack Quantity	1
Carton Quantity	10
Pallet Quantity	9600

Product Assets

Catalog [English]