

Product data sheet

Specifications



External rotary handle, TeSys GS, red handle, front mounting, 2 positions I-O, NEMA 3R, for GS 30 to 400A UL

GS2AH140

Product availability: Stock - Normally stocked in distribution facility

Main

| | |
|---------------------------|--|
| Range of Product | TeSys |
| Range | TeSys |
| Device short name | GS2AH |
| Product or Component Type | Rotary handle |
| Range compatibility | TeSys TeSys GS GS2EU TeSys TeSys GS GS2GU TeSys TeSys GS GS2JU TeSys TeSys GS GS2MU TeSys TeSys GS GS2QU |
| Type of operating handle | External frontal |
| Handle colour | Red |
| Handle front plate colour | Yellow |

Complementary

| | |
|--------------------------|---|
| Handle positions | O-I |
| Rotary handle padlocking | With |
| Switch rated current | 30 A 60 A 100 A 200 A 400 A |
| Standards | CSA UL |
| Net Weight | 0.53 lb(US) (0.24 kg) |

Environment

| | |
|---------------------------|------------|
| NEMA Degree of Protection | NEMA 3R/12 |
|---------------------------|------------|

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US10I1122640 |
| Discount Schedule | 0I11 |
| GTIN | 3389119411844 |
| Returnability | Yes |
| Country of origin | TN |

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|------------------------------|-------------------------|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg. | 1 |
| Package 1 Height | 1.97 in (5.000 cm) |
| Package 1 Width | 4.72 in (12.000 cm) |
| Package 1 Length | 6.30 in (16.000 cm) |
| Package weight(Lbs) | 8.713 oz (247.000 g) |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 15 |
| Package 2 Height | 11.81 in (30.000 cm) |
| Package 2 Width | 11.81 in (30.000 cm) |
| Package 2 Length | 15.75 in (40.000 cm) |
| Package 2 Weight | 9.149 lb(US) (4.150 kg) |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|


Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.



[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

|  Materials and Substances | |
|--|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant |
| REACH Regulation | REACH Declaration |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |

Use Again

|  Repack and remanufacture | |
|--|--|
| Take-back | No |
| WEEE |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |