



Pass and Seymour
15A 250V Heavy Duty Specification Grade Single Decorator Receptacles, White
Part No. 26661W

Heavy-Duty Decorator Spec Grade Single Receptacle Back and Side-Wire
15A 250V



Features & Benefits

Corrosion-resistant, plated steel strap locked into assembly to prohibit strap bending away from body. One-piece, brass, triple-wipe power contacts for lasting retention.

Heavy-duty compact design for easier installation and long lasting performance.

Impact-resistant nylon face.

Side and internal screw-pressure-plate back wire accepts #14 - #10 AWG solid or stranded wire.

Tri-drive terminal and mounting screws.

For covering patents, see www.legrand.us/patents.

Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current.

Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.

Terminal compartments isolated from each other for positive conductor containment.

All devices fit standard #26 opening wall plate.

Auto-ground clip assures positive ground.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click [here](#).

Specifications

General Info

| | | | |
|--------------------|----------------|-------------------|----------------|
| Product Line | Pass & Seymour | Color | White |
| UPC Number | 785007786064 | Country Of Origin | Mexico |
| Application Sector | Commercial | Standard | UL498, cUL CSA |

Dimensions

| | | | |
|-------------------|----------|------------------|----------|
| Product Width US | 1.322 in | Product Depth US | 1.188 in |
| Product Length US | 2.635 in | | |

Listing Agencies / 3rd Party Agencies

| | | | |
|--------------------|--------|------------|-----|
| cUL Listing Number | 140596 | cUL Listed | Yes |
|--------------------|--------|------------|-----|

Technical Information

| | | | |
|--------------------------|--------------------------|--------------------|--------------------|
| Dielectric Strength | Withstands 2000V minimum | Connection | Back and side wire |
| Number of Wires | 3 | Temperature Rating | -40° - 60° C |
| Amperage | 15 A | Number of Poles | Double Pole |
| Wire Size | 14 - 10 AWG | Voltage | 250.0 V |
| Environmental Conditions | Flammability: UL94 V2 | | |