




Topaz Specification Sheet

Description: Flexible Liquid Tight Metallic Conduit Reel

Standard Material: EF PVC Jacketed Steel Core Coil wrapped in clear plastic shrink wrapped

Standard Features: Corrosion resistant steel core for lasting mechanical protection. Oil Resistant. Sunlight Resistant. Smooth interior for easy wire pull-thru. Solid wood Reel attached with nylon threaded bolts.

Application: For use in damp or wet locations, suitable for commercial and industrial use. EF PVC jacket is oil and sunlight resistant. Non UL.



TOPAZ #	Trade Size	Inside Min (inch)	Inside Max (inch)	Outside Min (inch)	Outside Max (inch)
6100R	3/8"	.484	.504	.689	.709
6101R	1/2"	.622	.642	.819	.839
6102R	3/4"	.815	.835	1.032	1.051
6103R	1"	1.032	1.055	1.287	1.315
6104R	1-1/4"	1.370	1.394	1.630	1.661
6105R	1-1/2"	1.579	1.598	1.866	1.902
6105R150	1-1/2"	1.579	1.598	1.866	1.902
6106R	2"	2.020	2.043	2.339	2.374

TOPAZ CAT #	UPC#	SIZE	FEET REEL	UNIT CTN	SHIP CASE	WT/ CASE
6100R	85588	3/8"	1000	—	1000	182
6101R	82021	1/2"	1000	—	1000	296
6102R	85247	3/4"	500	—	500	148
6103R	85248	1"	200	—	200	96
6104R	85249	1-1/4"	200	—	200	192
6105R	85250	1-1/2"	100	—	100	79
6105R150	85527	1-1/2"	150	—	150	120
6106R	85251	2"	100	—	100	96

Approved by Quality Control: John Cavalieri



NEW YORK
925 Waverly Avenue
Holtsville, NY 11742
800-666-2852
Fax: 800-333-3488

CALIFORNIA
225 Parkside Drive
San Fernando, CA 91340
888-551-2852
Fax: 888-690-2852

FLORIDA
2020 West 26th Street
Jacksonville, FL 32209
800-666-2852
Fax: 800-333-3488