

45° Liquidtight Connectors With Grounding Lug - Malleable Iron

Features

- Liquidtight, raintight, oiltight
- Lay-in grounding lug
- Insulated throat protects conductors from abrasion damage
- Zinc electro plated for excellent durability

Applications

- Use to connect liquidtight conduit and terminate an external bonding conductor that runs parallel to the conduit
- The NEC code specifies length limitations and that the bonding jumper must be parallel to the conduit
- UL listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under: NEC 501-4(b), 502-4(a), (2)503-3(a) Class 1 Div.2, Class II Div.1 and 2, Class III Div.1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I



Standard Material


- Malleable iron
- Steel locknut
- Aluminum lug

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL 467 - UL 486A
- Fed. Spec: W-S-610E
- NEMA: GR 1-2017



Catalog Number	UPC	Conduit Size	Lug Size	Unit Carton	Ship Case	Weight/Case	A	Inches B	C
230SGR	86869	3/8"	14-4	5	50	16	1.18	1.39	2.51
231SGR	86870	1/2"	14-4	5	50	17	1.36	1.50	2.51
232SGR	86871	3/4"	14-4	2	50	24	1.61	1.73	2.70
233SGR	86872	1"	14-4	2	20	16	1.89	2.11	3.05
234SGR	86873	1-1/4"	14-4	2	20	24	2.39	2.56	3.65
235SGR	86874	1-1/2"	14-4	2	20	26	2.62	2.77	4.01
236SGR	86875	2"	14-4	2	20	37	3.24	3.38	4.64
237SGR	86876	2-1/2"	1/0-14	---	1	8	3.89	4.68	6.46
238SGR	86877	3"	1/0-14	---	1	11	4.74	5.33	7.01
239SGR	86878	3-1/2"	6/250	---	1	12	5.31	5.81	7.33
240SGR	86879	4"	6/250	---	1	14	5.82	6.42	8.20