



SKU: BGC-4/0P-DB

UPC: 0783669000689

Features & Benefits:

Description: Permaground Bronze Ground Clamp, Conductor Range 4/0-8, Pipe Sizes 1/2 to 1in, Ground Rod Sizes 1/2 to 1in, Rebar Sizes #3-#8, Parallel Lay-in, Direct Bury

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Parallel

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4/0 Str - 8 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Ground Rod Size	5/8
NPS/IPS Pipe Size	1
Rebar Size(s) Main	#8 (1)

Dimensions

Drive Size Main	NA
Drive Type Main	Internal Hex
Height (IN)	3.065
Height BX (IN)	2
Height (mm)	77.851
Length (IN)	2.492
Length (mm)	63.2968
Weight (LB)	0.55
Weight BX (LB)	5.6476
Width (IN)	0.815
Width BX (IN)	6.188
Width (mm)	20.701

Material and Finish

Clamping Hardware Material	Stainless steel
Conductor Material	Copper

Connector Finish	None
Insulation	NA
Material	Bronze
Wire Binding Hardware Material	Stainless steel

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-2
UPC Code	78366900068

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	8M24
UL / CULUS Specification	UL 467 Listed
UL File Number	E178441