

Eaton FH30

Catalog Number: FH30

Eaton A200/B100 heater, Used with Starter Sizes 0,1, and 2, A200/B100 Heater, NEMA, Ambient 3.43-3.73, 3.96-4.31A, Non-Comp 3.18-3.47, 3.88-4.22A, Used with Starter Sizes 0,1, and 2, Type A and B, Thermal and Fast Trip

General specifications



Product Name	Catalog Number
Eaton A200/B100 heater	FH30
UPC	Product Length/Depth
786678629773	2.1 in
Product Height	Product Width
0.8 in	1.3 in
Product Weight	Warranty
0.03 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Certifications	Catalog Notes
CSA Certified	Select heater coils based on full load current(FLA) shown on motor nameplate.
UL Listed	Heater coils are rated to protect 40 degree C rise and a service factor of 1.15, Single-Phase requires 2 heaters, Three-Phase Requires 3 heaters

Product specifications

Design

NEMA

Full load current range

Ambient 3.43-3.73, 3.96-4.31 A, Non-Comp 3.18-3.47, 3.88-4.22 A

Overload relay

Type A and B

Special features

Used with Starter Sizes 0,1, and 2

Type

A200/B100 Heater

Used with

Used with Starter Sizes 0,1, and 2

Trip type

Thermal and fast trip

Resources

Catalogs

Eaton's Volume 5—Motor Control and Protection

Installation instructions

Instructions for A200, A210, A250 size 6, two- or three-pole non-reversing or reversing motor controllers

Specifications and datasheets

Eaton Specification Sheet - FH30



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia