

Product data sheet

Specifications



Safety switch, double throw, non fusible, 2 pole, 3 wire, 240VAC, 200A, Type 3R, bolt/hub prov, with neut

DTU224NRB

Product availability: Stock - Normally stocked in distribution facility

Main

| | |
|---------------------------|---|
| Product | Double Throw Safety Switch |
| Duty Rating | General duty |
| Disconnect Type | Non-fusible disconnect switch |
| Factory Installed Neutral | Neutral (factory installed) |
| Number of Poles | 2 |
| Current Rating | 200 A |
| Voltage Rating | 240 V AC |
| Enclosure Rating | NEMA 3 |
| Motor power hp | 15 hp at 240 V AC 50-60 Hz for 1 phase motors |

Complementary

| | |
|-----------------------|---|
| Short-circuit current | 10 kA H or K |
| Fuse type | H or K |
| Mounting Type | Surface |
| Wire Size | AWG 6...300 kcmil copper or aluminium |
| Tightening torque | 340 lbf.in (38.4 N.m) (AWG 6...300 kcmil) |
| Depth | 10.63 in (270.002 mm) |
| Width | 24 in (609.6 mm) |
| Height | 32.5 in (825.5 mm) |
| Net Weight | 65.98 lb(US) (29.93 kg) |

Environment

| | |
|----------------|-----------|
| Certifications | UL Listed |
|----------------|-----------|

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US10DE100133 |
| Discount Schedule | 0DE1 |
| GTIN | 785901174523 |
| Returnability | Yes |
| Country of origin | MX |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

| | |
|------------------------|---------------------------|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg. | 1 |
| Package 1 Height | 10.6 in (27.0 cm) |
| Package 1 Width | 23.2 in (59.0 cm) |
| Package 1 Length | 33.9 in (86.0 cm) |
| Package weight(Lbs) | 69.860 lb(US) (31.688 kg) |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

| Environmental footprint | |
|--------------------------|---|
| Environmental Disclosure | Product Environmental Profile |

Use Better

| Materials and Substances | |
|--|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Compliant |
| REACH Regulation | REACH Declaration |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Use Again

| Repack and remanufacture | |
|--------------------------|--|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |

Technical Illustration

Dimensions

