



SKU: PTT-2L-350-Z

UPC: 0783669750256

Features & Benefits:

Description: Aluminum Pole Type Overhead Transformer Lug, Dual Rated, Conductor Range 350-10, 2 Ports, Left Handed

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	2
Number of Poles	1
Number of Ports / Wireways	2

Dimensions

Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	1.25
Height BX (IN)	2.25
Height (mm)	31.75
Length (IN)	3.018
Length (mm)	76.6572
Weight (LB)	0.008
Weight BX (LB)	0.9159
Width (IN)	4
Width BX (IN)	5
Width (mm)	101.6

Material and Finish

Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	5/8



General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 2
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366975025

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
-------------------	--

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	350 kcmil - 10 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil - 10 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol

Color

Color	Silver
-------	--------