

Product data sheet

Characteristics

LA26200AB

2P 200A 600V LA 1PHASE MOULDED CASE CIRCUIT BREAKER

Product availability : Stock - Normally stocked in distribution facility



Price* : 4053.00 USD



Main

Product or component type	Circuit breaker
Range of product	I-Line
Trip unit technology	Thermal-magnetic
Breaking capacity code	A

Complementary

Line Rated Current	200 A
Poles description	2P
Breaking capacity	25 kA at 600 V AC 42 kA at 240 V AC 30 kA at 480 V AC
System Voltage	250 V DC 600 V AC
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 1...600 kcmil (aluminium/copper) 1 cable(s) AWG 1...250 kcmil (aluminium/copper) 2 cable(s)
Terminal identifier	AL400LA
Magnetic hold current	1000 A
Magnetic tripping current	2000 A
Wiring configuration	2-wire
Phase connection	AB

Environment

Product certifications	UL listed CSA
------------------------	------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	01040 - LA/LH BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901562634
Nbr. of units in pkg.	1
Package weight(Lbs)	15.880000000000001
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1304 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------