

**Conduit Unions UNF & UNY Unions****1/2 INCH FEMALE-TO-MALE (F/M) ALUMINUM UNY UNION**

**Catalog Number** PRUNY105SA  
**UPC** 784011219360

**Description**

PVC coated UNY unions are used to connect conduit to a conduit fitting, junction box, or device enclosure. One end is a male thread and the other is female.

**Application**

- Applicable for Hazardous Locations

**Features**

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 13 trade sizes from 1/2" through 6"
- Sealing sleeves on all conduit openings
- Molded PVC gasket seals fitting

**General Information**


Trade Size	1/2
Material	ALUMINUM
Material	ALUMINUM
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane

**Dimensions**

Length (Inches)	2.38
Max Diameter (Inches)	2

**Standards**

CSA	C22.2 No. 30
NEC/CEC	Class II, Division 1, Groups E, F, G
NEC/CEC	Class I, Division 1 & 2, Groups A, B, C, D
NEC/CEC	Class III
NEC/CEC	Class II, Division 2, Groups F, G



UL 1203

E476062

**Technical Specification Documents**Specification Guide (1995 Master) AVAILABLE ON WEBSITESpecification Guide (2004 Master) AVAILABLE ON WEBSITEInstaller Certification and Tools AVAILABLE ON WEBSITEChemical Resistance Charts AVAILABLE ON WEBSITEPerformance Specifications AVAILABLE ON WEBSITE**Technical Information**Fitting Configuration F/MFitting Type UNIONProduct Category HAZARDOUS LOCATION FITTINGProduct Family Conduit Unions UNF & UNY UnionsRating Hazardous Location