

## SNAPConnect® Heavy Duty Hospital Grade Tamper-Resistant/Weather Resistant AUTOGUARD® Self-Test GFCI Receptacle, 20A, White

By Hubbell Wiring Device-Kellems  
Catalog # [SNAPGFTW83W](#)

Straight Blade SNAPConnect® WRTR GFCI Hospital Grade  
Receptacle, 20A



### Features

- Audible SNAP, indicates solid connection
- Patented shutter design for tamper-resistant protection
- Meets NEC requirements for TR (406.12) and WR (406.9), UV and corrosion resistance for harsh and damp applications
- Patented AUTOGUARD® Self-Test technology
- Protects against line and load reversal, no power to the face or downstream if device is miswired

### Application

Commercial Hospital Grade

### Specifications

Environmental Conditions	Weather Resistant
Industry Standard(s)	UL 943 and Meets All NEC® Requirements
Nema Rating	5-20R

### Conductor

Wire Size	SNAPConnect®
-----------	--------------

### Current

Phase	Single Phase
Current / Amperage Rating	20 A
Wattage	2500 W
Voltage Rating	125 VAC

### Dimensions

Length	1.48 in
Size	4.12 in x 1.75 in x 1.48 in

Width	1.75 in
Height	4.12 in
Dimensions	1.48 in x 1.75 in x 4.12 in

### General

Series	Hospital Grade
Color	White
Item Type	Self test GFCI receptacle Tamper-Resistant, Weather Resistant
Type	
Material	Nylon
Specifications	<ul style="list-style-type: none"><li>• Base - Nylon</li><li>• Face - Nylon</li><li>• Contacts - Brass</li><li>• Mounting Screws - Stainless Steel</li><li>• Mounting Strap - Brass</li><li>• Power Contacts - Brass</li></ul>
UPC	783585746333

### Logistics

Carton Quantity	10
Pallet Quantity	2240

### Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[Spanish, French, English\]](#)