


# Product data sheet

## Characteristics

# 9065SEO5

Overload Relay, Type S, melting alloy,  
separate mount overload, NEMA size 00, 0, 1,  
3 pole, 3 phase, 25A, 600VAC



## Main

Range of Product	Separate Mounting
Thermal overload type	Melting alloy

## Complementary

NEMA size	1
Number of thermal units required	3
Mounting Support	Panel
[Ue] rated operational voltage	600 V AC
Height	3.31 in (84.1 mm)
Width	3.53 in (89.7 mm)
Depth	3.97 in (100.8 mm)


## Ordering and shipping details

Category	21661-9065 A,C,F,G,S(NOT SS)
Discount Schedule	CP1
GTIN	785901878827
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.49 in (11.4 cm)
Package 1 Width	5.31 in (13.5 cm)
Package 1 Length	5.31 in (13.5 cm)
Package 1 Weight	16.32 oz (462.7 g)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------