

We MERSEN USA EP Corp.
374 Merrimac Street Newburyport, MA 01950 USA

Certify that products with the registered trade mark Mersen Ferraz Shawmut

Product type Low Voltage UL/CSA Fuses
Class L

Model Series Line A4BQ - Class L - Time-Delay

References please refer to page 2 for catalog number

comply with the EU RoHS (Restriction of Hazardous Substances) Directives:

RoHS directive N° 2011/65/UE

RoHS directive N° 2015/863

https://ec.europa.eu/environment/waste/rohs_eee/index_en.htm

and declare that the materials and the processes used to manufacture the above-mentioned parts do not contain any of the restricted substances beyond their specified limit at homogeneous material level as mentioned in the table:

Sl. No.	RoHS Restricted Substances	Max. Concentration
1.	Cadmium	0.01%
2.	Mercury	0.1%
3.	Lead	0.1%
4.	Chromium VI	0.1%
5.	Polybrominated biphenyls (PBB)	0.1%
6.	Polybrominated diphenyl ethers (PBDE)	0.1%
7.	Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
8.	Butyl benzyl phthalate (BBP)	0.1%
9.	Dibutyl phthalate (DBP)	0.1%
10.	Di-isobutyl phthalate (DIBP)	0.1%

Any exemptions are listed below and exemption validity dates are monitored by Mersen.

The information provided below is based on data obtained through ongoing due diligence with our suppliers. In some cases, the information may not yet represent full coverage of our supply chain. Mersen reserves the right to update or amend this declaration as additional data becomes available, or verification processes are completed.

This declaration is not an EU or UKCA declaration of conformity, Mersen USA EP Corp. is providing RoHS conformity to all product ranges even if they are out of the scope of the directive with the same level of compliance on substances restrictions and corresponding exemptions.

Date / Location : 18.05.2026 / Newburyport

Name : Tim KAPPEN

Position / Signature :

Sr. Manager Quality
For the president and by delegation



COMP-016664

Catalog number list

Item number	ROHS exemption
A4BQ900	
A4BQ1000	
A4BQ1200	
A4BQ900-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ1000-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ1200-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ1350	
A4BQ1400	
A4BQ1500	
A4BQ1600	
A4BQ1350-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ1400-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ1500-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ1600-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ1900	
A4BQ1800	
A4BQ2000	
A4BQ1800-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ2000-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ2500	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ2500-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ2001-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ2200-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ2501	
A4BQ3000	
A4BQ3000-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ3500	
A4BQ4000	
A4BQ3800	
A4BQ3500-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ3800-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ4000-TA	6(c) - Copper alloy containing up to 4% lead by weight

A4BQ5000	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ5000-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ300	
A4BQ6000	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ6000-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ100-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ150-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ200-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ250-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ300-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ350-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ400-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ450-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ500-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ600-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ650	
A4BQ700	
A4BQ750	
A4BQ800	
A4BQ601	
A4BQ601-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ650-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ700-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ750-TA	6(c) - Copper alloy containing up to 4% lead by weight
A4BQ800-TA	6(c) - Copper alloy containing up to 4% lead by weight