

Reducing Bushings and Couplings

1 TO 3/4 INCH REDUCING COUPLING



Catalog Number	PRREC32
UPC	784011209033

Description

PVC coated reducing couplings are used to connect two pieces of conduit of different size.

Application

- Used to connect two pieces of conduit of different size.

Features

- Used to connect two pieces of conduit of different size

General Information

Trade Size	1
Material	FERROUS METAL
Material	FERROUS METAL

Dimensions

Nominal Weight (Pounds)	0.5
Pipe Size (Inches)	1 to 3/4

Standards

NEC/CEC	Class I, Division 1 & 2, Groups A, B, C, D
NEC/CEC	Class II, Division 1, Groups E, F, G
NEC/CEC	Class III
NEC/CEC	Class II, Division 2, Groups F, G

Technical Specification Documents



Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Installer Certification and Tools	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Chemical Resistance Charts	AVAILABLE ON WEBSITE
----------------------------	----------------------

Performance Specifications	AVAILABLE ON WEBSITE
----------------------------	----------------------

Technical Information

Fitting Configuration	REDUCING
-----------------------	----------

Fitting Type	COUPLING
--------------	----------

Product Category	FITTING
------------------	---------

Product Family	Reducing Bushings and Couplings
----------------	---------------------------------

Trade Size Range	1 to 3/4
------------------	----------

Notes

- All REC, RE, and PLGs meet Class I, Division 1 & 2, Groups C, D. REs & PLGs meet the above standards only when used in conjunction with hazardous location fittings.