



Color: Bronze

Weight: 5.5 lbs

Project:

Type:

Prepared By:

Date:

Driver Info

Type	Constant
120V	0.66A
208V	0.40A
240V	0.35A
277V	0.32A
Input Watts	50.5-83W

LED Info

Watts	80/70/60/50W
Color Temp	3000K/4000K/5000K
Color Accuracy	81-84 CRI
L70 Lifespan	100,000 Hours
Lumens	7,193-12,772 lm
Efficacy	127.6-171 lm/W

Technical Specifications**Field Adjustability****Optical Field Adjustability:**

90°, 75° and 55°

Field Adjustable:Field Adjustable Light Output:
80W/70W/60W/50W (factory default 80W)

Color Temperature Selectable:

3000K, 4000K and 5000K (factory default 4000K)

Compliance**UL Listed:**

Suitable for wet locations

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

IP Rating:

Ingress protection rating of IP65 for dust and water

DLC Listed:

This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.

DLC Product Code: S-HDQRO9

Electrical**Driver:**80W: Class 1, Constant Current, 120-277V, 50/60 Hz,
120V: 0.66A, 208V: 0.40A, 240V: 0.35A, 277V: 0.32A70W: Class 1, Constant Current, 120-277V, 50/60 Hz,
120V: 0.58A, 208V: 0.35A, 240V: 0.31A, 277V: 0.28A60W: Class 1, Constant Current, 120-277V, 50/60 Hz,
120V: 0.51A, 208V: 0.31A, 240V: 0.28A, 277V: 0.26A50W: Class 1, Constant Current, 120-277V, 50/60 Hz,
120V: 0.44A, 208V: 0.26A, 240V: 0.24A, 277V: 0.22A**Dimming Driver:**

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

THD:

8.71% at 120V, 5.57% at 277V

Power Factor:

88.9% at 120V, 99.4% at 277V

Surge Protection:

L/N-PE: 6kV, L-N: 6kV

Photocell:

Integrated photocell included with on/off switch

LED Characteristics**LEDs:**

Long-life, high-efficacy, surface-mount LEDs

Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Color Consistency:3000K & 5000K: 5-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color
4000K: 7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color**Performance****Lifespan:**

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Performance Data:[Click here for the X22-80 performance data](#)**Construction****Cold Weather Starting:**

The minimum starting temperature is -30°C (-22°F)

Technical Specifications (continued)**Maximum Ambient Temperature:**

Suitable for use in up to 50°C (122°F)

Housing:

Die-cast aluminum

Mounting:

Robust knuckle mount with 180° adjustable swivel arm. Tilt angle in 10° increments. Trunnion kit is included.

Lens:

Tempered glass

Effective Projected Area:

1 Fixture: 0.249 ft²
2 Fixtures at 90°: 0.587 ft²
2 Fixtures at 180°: 0.498 ft²
3 Fixtures at 90°: 0.836 ft²
4 Fixtures at 90°: 0.836 ft²

Finish:

Formulated for high durability and long-lasting color

Green Technology:

Mercury and UV free. RoHS-compliant components.

Other**Note:**

All values are typical (tolerance +/- 10%)



5 Yr Limited Warranty:

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

DLC Premium listed

IP65 Rated

100,000-Hour LED lifespan

5-Year, limited warranty

Ordering Matrix

Family	Wattage	Color Temp	Mounting	Finish	Beam Angle	Voltage	Options
X22	80	Blank = 3000K/4000K/5000K CCT Adjustable	Blank	Blank = Knuckle Mount Installed with Yoke Kit Included	Blank = Selectable Beam Angle (Medium to Very Wide Flood 55-100°)	Blank = 120-277V /480 = 480V, 0-10V Dimming	Blank = Selectable On/Off Photocell
	35 = 35/30/25/20W						
	60 = 60/50/40/30W						
	80 = 80/70/60/50W						
	150 = 150/125/100/75W						
	250 = 250/220/190/160W						
	320 = 320/280/240/200W						
	420 = 420/380/340/300W						
	500 = 500/450/420/380W						
	20 = 20/17/13/10W						

X22-20 & X22-35: Knuckle mount installed with yoke mount included.

X22-60 & X22-80: Knuckle mount installed with trunnion mount included.

150W: Slipfitter mount installed with trunnion mount included.