



SKU: BGC-1DB

UPC: 0783669009903

Features & Benefits:

Description:Permaground Brass Ground Clamp, Conductor Range 2-10, Pipe Sizes 1/2 to 1in, UL, Direct Bury

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Wire Orientation	Parallel

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2 Str - 10 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
NPS/IPS Pipe Size	1/2

Dimensions

Drive Size Main	NA
Height (IN)	2.542
Height BX (IN)	3.75
Height (mm)	64.5668
Length (IN)	2.218
Length (mm)	56.3372
Weight (LB)	0.17
Weight BX (LB)	4.995
Width (IN)	0.641
Width BX (IN)	6
Width (mm)	16.2814

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Silicon bronze



Additional Technical Specifications

Conductor Type

Solid

Bolt and Screw Sizes

Number of Wire Binding Screws per Port

1

Wire Binding Screw Size

NA

General

Bag Quantity

1

Carton Quantity Description

STD PACK QTY 25

Direct Burial

Yes

Dual Rated

No

NEMA Code

S-573-2

UPC Code

78366900990

Testing Standards

CSA File Number

LR-701570

CSA Standard

C22.2 No. 41

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -
www.P65warnings.ca.gov

UL Control Number

8M24

UL / CULUS Specification

UL 467 Listed

UL File Number

E158587