

Product data sheet

Characteristics

UH7213C

Meter socket, ringless, 3 phase, 4 wire, 7 jaws,
Series A, lever bypass, jaw release



Main

Product or Component Type	Meter Socket
Meter socket type	Ringless
Hub type	A ACP closing plate

Complementary

Meter socket rated current	200 A
Number of jaws	7 with jaw release
Bypass type	Lever bypass
Phase	3 phase
[Ue] rated operational voltage	600 V AC
Enclosure Material	Steel
Electrical connection	Lugs 0.5" hex
Service feed location	OH UG
Wiring configuration	3-wire
Device mounting	Surface
AWG gauge	AWG 6...350 kcmil aluminium/copper)line side AWG 6...350 kcmil aluminium/copper)service ground

Environment

Product Certifications	UL Listed
Enclosure Rating	NEMA 3R

Ordering and shipping details

Category	00039-METER SOCKETS & HUBS
Discount Schedule	DE4
GTIN	785901690528
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.80 in (14.732 cm)
Package 1 Width	13.80 in (35.052 cm)
Package 1 Length	20.50 in (52.07 cm)
Package 1 Weight	23.21 lb(US) (10.528 kg)

Offer Sustainability

California proposition 65

WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

EU RoHS Directive

Under investigation

Contractual warranty

Warranty

18 months