

90° Liquidtight Connectors With Grounding Lug - Malleable Iron

Features

- Liquidtight, raintight, oiltight
- Lay-in grounding lug
- Insulated throat protects conductors from abrasion damage
- Zinc electro plated for excellent durability

Applications

- Use to connect liquidtight conduit and terminate an external bonding conductor that runs parallel to the conduit
- The NEC code specifies length limitations and that the bonding jumper must be parallel to the conduit
- UL listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under: NEC 501-4(b), 502-4(a), (2)503-3(a) Class 1 Div.2, Class II Div.1 and 2, Class III Div.1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I

Standard Material


- Malleable iron
- Steel locknut
- Aluminum lug

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL 467 - UL 486A
- Fed. Spec: W-S-610E
- NEMA: GR 1-2017



Catalog Number	UPC	Conduit Size	Lug Size	Unit Carton	Ship Case	Weight/Case	A	Inches B	C
490SGR	86880	3/8"	14-4	5	50	17	1.18	1.96	2.47
491SGR	86881	1/2"	14-4	5	50	24	1.36	2.10	2.54
492SGR	86882	3/4"	14-4	2	20	16	1.61	2.45	2.82
493SGR	86883	1"	14-4	2	20	17	1.89	2.83	3.08
494SGR	86884	1-1/4"	14-4	2	20	25	2.39	3.15	3.53
495SGR	86885	1-1/2"	14-4	2	20	29	2.62	3.50	4.17
496SGR	86886	2"	14-4	2	20	42	3.24	4.02	4.69
497SGR	86887	2-1/2"	1/0-14	---	1	9	3.89	6.23	6.74
498SGR	86888	3"	1/0-14	---	1	11	4.74	6.91	7.52
499SGR	86889	3-1/2"	6/250	---	1	13	5.31	7.57	7.93
500SGR	86890	4"	6/250	---	1	15	5.82	8.07	8.72