


Project:

Type:

Prepared By:

Date:



UPC: 019813751610

Features and Benefits

- Replaces 18W/26W/32W 2G11 CFL Lamps
- Ballast Bypass. Integral Driver enables lamp to be wired directly to line voltage without need for an external driver or ballast
- 50,000 hour Lifespan
- Environmentally friendly, no mercury used
- UL Classified, DLC Listed
- Rated for use in enclosed and open fixtures in dry or damp locations
- 5 Year No Compromise Warranty

Technical Specifications

Performance

Product Type:
Compact

Input Wattage:
17W

Wattage Equivalency:
40W Fluorescent

Lumens:
2,200lm

Efficacy:
129lm/W

L70 Lifespan:
50,000 Hours

Electrical

THD:
<20%

Power Factor:
0.9

Dimmable:
Not suggested for dimming applications

Operating Temperature:
-20°C to 45°C (-4°F to 113°F)

Input Voltage:
120-277V AC

Operating Frequency:
50/60Hz

Construction

Shape:
PLL

Finish:
Frosted

For Use Outdoors in Open Fixtures:
No

LED Characteristics

Color Temperature:
4000K Cool White

Color Accuracy (CRI):
82 CRI

Installation

Base Type:
2G11

Installation Type:
Type B, Ballast Bypass

Installation Orientation:
Horizontal

Other

5-Year, No-Compromise Warranty:
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance

UL Recognized:
Yes

Technical Specifications (continued)

UL Classified:
Yes

NSF Listed:
Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones. Tube guard required in open fixtures.

Certification Model Number:
PLL-17-840-BYP

California Energy Commission (CEC) Status:
Lawful for Sales in California


Application:
Suitable for damp locations and totally enclosed fixtures.

DLC Listed:
This product family is listed with the DesignLights Consortium (DLC). Individual SKUs within this family may carry either a DLC Standard or DLC Premium qualification. Please refer to the individual product specification sheet or the DLC Qualified Products List (QPL) at designlights.org to confirm the qualification status of a specific SKU prior to specification or purchase.

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	25	23.6	9.8	7
PALLET	1400	47.2	39.4	40.2

Wiring Diagram



Dimension

