



Pass and Seymour
30A NEMA L1630 Single Receptacle
Part No. L1630R

Turnlok® Single Receptacle 4-Wire 30A 3-Phase 480V



Features & Benefits

Compact, impact-resistant nylon face and body are ultrasonically welded together for unrivaled strength.

One piece, high-grade brass contacts offer excellent conductivity and heat-rise resistance.

Single-piece, solid brass mounting strap is free of easily loosened rivets found on other brands.

Accepts #14 - #10 AWG.

Face color coding by voltage facilitates locating and mating of proper devices.

Clearly marked NEMA configuration, rating, and third-party listing on each unit's face.

Side and external screw-pressure-plate back wire capability.

Specifications

General Info

Product Line	Pass & Seymour	Color	Black
UPC Number	785007163056	Country Of Origin	Mexico
Number of Receptacles	1	Features	Brass Mounting Strap, Impact Resistant
Outlet Type	Locking	Application Sector	Industrial
Wall Plate Included	No	Standard	UL 498
Warranty Type	1-Year Limited Warranty		

Dimensions

Product Width US	1.61 in	Product Depth US	1.28 in
------------------	---------	------------------	---------

Product Height US 2.42 in

Listing Agencies / 3rd Party Agencies

cULus Listing Number 140596 cULus Listed Yes

Additional Information

Product Environmental Profile Yes

Technical Information

Connection Location Back and Side Number of Wires 4

Amperage 30 A Number of Poles Double Pole

Wire Size 14 - 10 AWG Indoor/Outdoor Indoor

NEMA Configuration Code L16-30R Wire Connection Type Screw Terminals

Voltage 480.0 V
