



Actual

Catalog Number: CPS341212
Product ID: 7TCA298010R0381
EAN Number: 05020963036484
Status: Active

Hinged Protective Shroud, Straight, Conduit Size A: NC12/NW10, Side B: NC12/NW10, Internal Diameter 35mm, Operating Temperature -40 to 120 Degrees Celsius, RoHS Compliant, IP40 Rating, Very High UV Protection, Polyamide (Nylon), Black

North American Specifications (UNSPSC)

UNSPSC	39131707 Electrical conduit coupling
IGCC	5548 Electrical conduit coupling
Brand Name	Harnessflex
Type	Protective Shroud for Conduit
Application	Protection for In-Line Connectors, Fuse Links, Circuit Breakers and Splicing Areas
Standard	RoHS Compliant, Complies with End of Life Vehicle (ELV) Directive EU 2000/53/EC
Trade Size	NC12/NW10
Inside Diameter	35mm
Installation Type	Externally Hinged
Material	Polyamide/Nylon
Connection	Straight
Color	Black

European Specifications (ETIM)

ETIM	EC001172 Coupler for corrugated plastic hoses
Material	Plastic
Material quality	Polyamide (PA)
Operating temperature	-40-+120°C
Degree of protection (IP)	IP40
Model	Straight
Nominal size	12-12mm
Colour	Black

Packaging

Outer Quantity	100
Outer Dimensions (inches)	1x1x1
Weight Uom	0.05 lbs. Each

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com