



**SKU:** PET-8-500-Z

**UPC:** 0783669710229

#### **Features & Benefits:**

**Description:** Aluminum Spade Type Transformer Lug, Dual Rated, Conductor Range 500-2, 8 Ports

## Specs

### Additional Class Attributes

<b>Connection</b>	Mechanical
<b>Contains DE-OX®</b>	No
<b>Number of Conductors</b>	8
<b>Number of Poles</b>	1
<b>Number of Ports / Wireways</b>	8

### Dimensions

<b>Drive Size Main</b>	5/16
<b>Drive Type Main</b>	Internal Hex
<b>Height (IN)</b>	1.625
<b>Height BX (IN)</b>	3.75
<b>Height (mm)</b>	41.275
<b>Length (IN)</b>	12.406
<b>Length (mm)</b>	315.1124
<b>Weight (LB)</b>	1.764
<b>Weight BX (LB)</b>	5.6869
<b>Width (IN)</b>	1
<b>Width BX (IN)</b>	6.5
<b>Width (mm)</b>	25.4

### Material and Finish

<b>Conductor Material</b>	Aluminum
<b>Connector Finish</b>	Tin
<b>Insulation</b>	NA
<b>Material</b>	Aluminum
<b>Wire Binding Hardware Finish</b>	Tin
<b>Wire Binding Hardware Material</b>	Aluminum

### Additional Technical Specifications

<b>Conductor Type</b>	Stranded
-----------------------	----------

### Bolt and Screw Sizes

<b>Number of Wire Binding Screws per Port</b>	1
---	---

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366971022

### Testing Standards

ANSI Specification	ANSI C119.6
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL File Number	NA

### Color

Color	Silver
-------	--------

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	500 kcmil - 2 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 2 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA