



SKU: IK3-6

UPC: 0783669813555

Features & Benefits:

Description: Three Wire Copper Split Bolt, Conductor Range for Equal Main & Tap 6 Sol - 10 Sol, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	3
Number of Poles	1

Dimensions

Drive Size Main	1/2
Drive Type Main	External Hex
Height (IN)	0
Height BX (IN)	2
Length (IN)	0
Weight (LB)	0.055
Weight BX (LB)	5.647
Width (IN)	0
Width BX (IN)	6.1875
Wire Diameter Range Primary (IN)	0.102 - 0.162

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA

General

Bag Quantity	1
--------------	---

Carton Quantity Description	STD PACK QTY 100
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-4
UPC Code	78366981355

Testing Standards

CSA File Number	LR-701570
CSA Standard	C22.2 No. 188
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	460C
UL / CULUS Specification	UL 467 Listed
UL File Number	E12822

Environment and Temperature

Temperature Rating	90°C
---------------------------	------

Color

Color	Copper
--------------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	NA
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range for Equal Run & Tap Str	6 Str - 8 Str
Conductor Range for Equal Run & Tap Sol	6 Sol - 10 Sol
Conductor Range for Minimum Tap with Maximum Run	16 Sol
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	35 kV
-----------------------	-------