

Specifications



Eaton AH7810GD

Eaton manual motor controller, #14-10 AWG, 30A, Wall, 600V, Front wired screw and clamp, Maintained contact, Gray, NEMA 1, Enclosure: SS, Three-pole, Single-gang, Two-position, Three-phase, Toggle, Copper-alloy terminal, Single-throw



General specifications

PRODUCT NAME	Eaton manual motor controller
CATALOG NUMBER	AH7810GD
UPC	040893598604
PRODUCT LENGTH/DEPTH	4.75 in
PRODUCT HEIGHT	3.25 in
PRODUCT WIDTH	3 in
PRODUCT WEIGHT	1.6 lb
COMPLIANCES	NAFTA RoHS Compliant
CERTIFICATIONS	cULus Listed

Product specifications

NEMA RATING	1
ENCLOSURE	NEMA 1
SPECIAL FEATURES	With NEMA 1 enclosure
TYPE	Manual motor controller
AMPERAGE RATING	30A
VOLTAGE RATING	600 V
NUMBER OF POLES	Three-pole
PHASE	Three-phase
ENCLOSURE MATERIAL	Stainless steel
APPLICATION	Industrial
DEVICE GRADE	Industrial
WIRING METHOD	Front wired screw and clamp
CONTACT TYPE	Maintained
SWITCH TYPE	Toggle switch
MOUNTING METHOD	Wall
CLOSURE TYPE	Maintained
NUMBER OF GANGS	1
NUMBER OF POSITIONS	2
ALLOWABLE WIRE SIZE	#14-10 AWG
OPERATING TEMPERATURE	-20 to 65 °C
MATERIAL	Glass-filled nylon
TERMINATION STYLE	Front screw and clamp
THROW	Single-throw
TERMINALS	Copper-alloy, brass screw
COLOR	Gray

Resources

CATALOGS

[Arrow Hart Buyers Guide](#)
[Section E](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - AH7810GD](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

