



**SKU:** CTL-350

**UPC:** 0783669145724

**Features & Benefits:**

**Description:** Surecrimp Copper Compression Sleeve, Conductor Size 350, Long Barrel, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

|                           |             |
|---------------------------|-------------|
| Barrel Marking            | Ink         |
| Barrel Type               | Long        |
| Connecting Angle          | 180°        |
| Connection                | Compression |
| Contains DE-OX®           | No          |
| Flared End                | No          |
| ILSCOs Die Catalog Number | ILD-71      |
| ILSCOs Die Index Number   | I-71        |
| Number of Conductors      | 1           |
| Sight Window              | No          |
| Slotted                   | No          |

### Dimensions

|                       |         |
|-----------------------|---------|
| Height (IN)           | 0.89    |
| Height BX (IN)        | 2.25    |
| Height (mm)           | 22.606  |
| Inside Diameter (IN)  | 0.703   |
| Inside Diameter (mm)  | 17.8562 |
| Length (IN)           | 4.125   |
| Length (mm)           | 104.775 |
| Outside Diameter (IN) | 0.89    |
| Outside Diameter (mm) | 22.606  |
| Weight (LB)           | 0.351   |
| Weight BX (LB)        | 3.0114  |
| Width (IN)            | 0.89    |
| Width BX (IN)         | 5       |
| Width (mm)            | 22.606  |

### Conductor Ranges

|                                                        |                     |
|--------------------------------------------------------|---------------------|
| Conductor Range AL Stranded (Primary, run, main, line) | NA                  |
| Conductor Range CU Solid (Primary, run, main, line)    | NA                  |
| Conductor Range CU Stranded (Primary, run, main, line) | 350 kcmil           |
| Conductor Range AL Solid (Primary, run, main, line)    | NA                  |
| Expanded Conductor Range                               | 350 kcmil - 3/0 Str |
| Flex Conductor Range                                   | 250 I,K,M 262.2 DLO |

### Material and Finish

|                    |        |
|--------------------|--------|
| Conductor Material | Copper |
| Connector Finish   | Tin    |
| Material           | Copper |

### Additional Technical Specifications

|                |      |
|----------------|------|
| Conductor Type | Flex |
|----------------|------|

### General

|                             |                |
|-----------------------------|----------------|
| Bag Quantity                | 1              |
| Carton Quantity Description | STD PACK QTY 6 |
| Direct Burial               | Yes            |
| Dual Rated                  | No             |
| NEMA Code                   | S-588-1        |
| UPC Code                    | 78366914572    |

### Bolt and Screw Sizes

|                         |    |
|-------------------------|----|
| Mounting Bolt/Stud Size | NA |
|-------------------------|----|

### Testing Standards

|                          |                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| CSA File Number          | LR-29601                                                                                                            |
| CSA Standard             | C22.2 No. 65-03                                                                                                     |
| NEBS Rating              | Level 3                                                                                                             |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| UL Control Number        | 453G                                                                                                                |
| UL / CULUS Specification | UL 486A/B Listed                                                                                                    |
| UL File Number           | E6207                                                                                                               |

### Environment and Temperature

|                    |      |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

### Color

|            |        |
|------------|--------|
| Color      | Silver |
| Color Code | Red    |

### Voltage

|                |       |
|----------------|-------|
| Voltage Rating | 35 kV |
|----------------|-------|